

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 8.2 Revision Date 27.09.2020 Print Date 28.02.2021

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Acetone

Product Number : V800023 Brand : Vetec

Index-No. : 606-001-00-8

REACH No. : 01-2119471330-49-XXXX

CAS-No. : 67-64-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Ireland Ltd.

Vale Road, Arklow Eircode Y14EK18 CO WICKLOW IRELAND

Telephone : +353 402-20300

E-mail address : TechnicalService@merckgroup.com

1.4 Emergency telephone

Emergency Phone # : +(353)-19014670 (CHEMTREC)

#### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225

Eye irritation (Category 2), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

 $\vee$   $\vee$ 

Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapor.

Vetec- V800023 Page 1 of 9



H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Molecular weight : 58.08 g/mol CAS-No. : 67-64-1 EC-No. : 200-662-2 Index-No. : 606-001-00-8

Component	Classification	Concentration
acetone		
	Flam. Liq. 2; Eye Irrit. 2; STOT SE 3; H225, H319, H336 Concentration limits: >= 20 %: STOT SE 3, H336;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

# **SECTION 4: First aid measures**

# 4.1 Description of first-aid measures

#### **General advice**

Consult a physician. Show this material safety data sheet to the doctor in attendance.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

# If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Vetec- V800023 Page 2 of 9



# 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# 4.3 Indication of any immediate medical attention and special treatment needed

No data available

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

# Suitable extinguishing media

Dry powder Dry sand

# Unsuitable extinguishing media

Do NOT use water jet.

# 5.2 Special hazards arising from the substance or mixture

Carbon oxides

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

# 5.4 Further information

Use water spray to cool unopened containers.

#### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

For personal protection see section 8.

#### **6.2 Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

# 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

# 6.4 Reference to other sections

For disposal see section 13.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Vetec- V800023

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in cool place.

Page 3 of 9



# 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
acetone	67-64-1	TWA	500 ppm 1,210 mg/m3	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
	Remarks	Indicative		
		OELV - 8 hrs (TWA)	500 ppm 1,210 mg/m3	Ireland. List of Chemical Agents and Occupational Exposure Limit Values - Schedule 1

# 8.2 Exposure controls

# **Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

# Personal protective equipment

# **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

# Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

#### **Body Protection**

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

# Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

# **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

MERCK

# **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties 9.1

a) Appearance Form: clear, liquid

Color: colorless

b) Odor pungent, weakly aromatic

No data available c) Odor Threshold

5 - 6 at 395 g/l at 20 °C d) pH

Melting point: -94.8 °C e) Melting

point/freezing point

56.0 °C at 1013 hPa Initial boiling point f) and boiling range

-17.0 °C - closed cup g) Flash point

h) Evaporation rate No data available No data available

Flammability (solid,

gas)

i)

Upper/lower

flammability or

Upper explosion limit: 13 %(V) Lower explosion limit: 2 %(V)

explosive limits 533.3 hPa at 39.5 °C k) Vapor pressure

245.3 hPa at 20.0 °C

Vapor density No data available I)

m) Relative density 0.79 g/cm3 at 20 °C

n) Water solubility soluble, in all proportions

o) Partition coefficient: No data available

n-octanol/water

p) Autoignition 465.0 °C

temperature

q) Decomposition temperature

Distillable in an undecomposed state at normal pressure.

No data available r) Viscosity No data available s) Explosive properties

No data available t) Oxidizing properties

#### 9.2 Other safety information

0.01 µS/cm at 20 °C Conductivity 23.2 mN/m at 20.0 °C Surface tension

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No data available

# 10.2 Chemical stability

Stable under recommended storage conditions.

Vetec- V800023 Page 5 of 9

# 10.3 Possibility of hazardous reactions

No data available

#### 10.4 Conditions to avoid

Heat, flames and sparks.

# 10.5 Incompatible materials

Bases, Oxidizing agents, Reducing agents, Acetone reacts violently with phosphorous oxychloride. Strong oxidizing agents

# 10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides In the event of fire: see section 5

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

# **Acute toxicity**

LD50 Oral - Rat - female - 5,800 mg/kg

Remarks: (ECHA)

LC50 Inhalation - Rat - 4 h - 76 mg/l

Remarks: Unconsciousness Drowsiness Dizziness (External MSDS)

LD50 Dermal - Rabbit - 20,000 mg/kg

Remarks: (IUCLID)

# Skin corrosion/irritation

Skin - Rabbit

Result: Mild skin irritation - 24 h

(Draize Test) Remarks: (RTECS)

# Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation - 24 h

(Draize Test) Remarks: (RTECS)

# Respiratory or skin sensitization

Maximization Test - Guinea pig Result: Not a skin sensitizer.

Remarks: (ECHA)

Chronic exposure may cause dermatitis.

# Germ cell mutagenicity

Mutagenicity (mammal cell test): chromosome aberration.

Chinese hamster ovary cells

Result: negative Ames test

Salmonella typhimurium

Result: negative

In vitro mammalian cell gene mutation test

Mouse lymphoma test Result: negative

### Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

# Reproductive toxicity

No data available

# Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Narcotic effects

# Specific target organ toxicity - repeated exposure

No data available

# **Aspiration hazard**

No data available

#### **Additional Information**

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption:

Headache, Salivation, Nausea, Vomiting, Dizziness, narcosis, Coma

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Kidney - Irregularities - Based on Human Evidence Skin - Dermatitis - Based on Human Evidence

# **SECTION 12: Ecological information**

# 12.1 Toxicity

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) -

6,210 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia

and other aquatic invertebrates

R

static test LC50 - Daphnia pulex (Water flea) - 8,800 mg/l - 48 h

Remarks: (ECHA)

Toxicity to algae

static test NOEC - M.aeruginosa - 530 mg/l - 8 d

(DIN 38412)

Remarks: (maximum permissible toxic concentration)(IUCLID)

Toxicity to bacteria static test EC50 - activated sludge - 61.15 mg/l - 30 min

(OECD Test Guideline 209)

#### 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 91 % - Readily biodegradable.

(OECD Test Guideline 301B)

Biochemical Oxygen 1,850 mg/g

Demand (BOD) Remarks: (IUCLID)

Chemical Oxygen 2,070 mg/g

Demand (COD) Remarks: (IUCLID)

Theoretical oxygen 2,200 mg/g demand Remarks: (Lit.)

# 12.3 Bioaccumulative potential

Does not bioaccumulate.

Vetec- V800023 Page 7 of 9

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

Additional ecological No data available information

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

#### Contaminated packaging

Dispose of as unused product.

# **SECTION 14: Transport information**

#### 14.1 UN number

ADR/RID: 1090 IMDG: 1090 IATA: 1090

# 14.2 UN proper shipping name

ADR/RID: ACETONE IMDG: ACETONE IATA: Acetone

# 14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

#### 14.4 Packaging group

ADR/RID: II IMDG: II IATA: II

#### 14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

# 14.6 Special precautions for user

No data available

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles

Vetec- V800023 Page 8 of 9

(Annex XVII)

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

# 15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

#### **SECTION 16: Other information**

#### Full text of H-Statements referred to under sections 2 and 3.

EUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

#### **Further information**

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.





Page 9 of 9

Vetec- V800023