

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 7.2
Revision Date 27.02.2021
Print Date 28.02.2021**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Methanol

Product Number : 34860

Brand : SIGALD

Index-No. : 603-001-00-X

REACH No. : 01-2119433307-44-XXXX

CAS-No. : 67-56-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Ireland Ltd.
Vale Road, Arklow
Eircode Y14EK18
CO WICKLOW
IRELAND

Telephone : +353 402-20300

E-mail address : TechnicalService@merckgroup.com

1.4 Emergency telephone

Emergency Phone # : +(353)-19014670 (CHEMTREC)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Flammable liquids (Category 2), H225

Acute toxicity, Oral (Category 3), H301

Acute toxicity, Inhalation (Category 3), H331

Acute toxicity, Dermal (Category 3), H311

Specific target organ toxicity - single exposure (Category 1), Eyes, Central nervous system, H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements**Labelling according Regulation (EC) No 1272/2008**

Pictogram



Signal word	Danger
Hazard statement(s)	
H225	Highly flammable liquid and vapor.
H301 + H311 + H331	Toxic if swallowed, in contact with skin or if inhaled.
H370	Causes damage to organs (Eyes, Central nervous system).
Precautionary statement(s)	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.
Supplemental Hazard Statements	none

Reduced Labeling (<= 125 ml)

Pictogram



Signal word	Danger
Hazard statement(s)	
H370	Causes damage to organs.
H301 + H311 + H331	Toxic if swallowed, in contact with skin or if inhaled.
Precautionary statement(s)	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.
Supplemental Hazard Statements	none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms	: Methyl alcohol
Formula	: CH ₄ O
Molecular weight	: 32.04 g/mol
CAS-No.	: 67-56-1
EC-No.	: 200-659-6
Index-No.	: 603-001-00-X

Component	Classification	Concentration
-----------	----------------	---------------

Methanol			
CAS-No.	67-56-1	Flam. Liq. 2; Acute Tox. 3;	<= 100 %
EC-No.	200-659-6	STOT SE 1; H225, H301,	
Index-No.	603-001-00-X	H331, H311, H370 Concentration limits: >= 10 %: STOT SE 1, H370; 3 - < 10 %: STOT SE 2, H371;	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

Notes to physician

Dizziness Drowsiness metabolic acidosis Blurred vision Seizures. Coma Blindness death

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

No data available

5.2 Special hazards arising from the substance or mixture

Carbon oxides
Combustible.

5.3 Advice for firefighters

No data available

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For personal protection see section 8.

6.2 Environmental precautions

No data available

6.3 Methods and materials for containment and cleaning up

No data available

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

No data available

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Methanol	67-56-1	TWA	200 ppm 260 mg/m ³	Europe. Indicative occupational exposure limit values
	Remarks	Indicative Identifies the possibility of significant uptake through the skin		
		OELV - 8 hrs (TWA)	200 ppm 260 mg/m ³	Ireland. List of Chemical Agents and Occupational Exposure Limit Values - Schedule 1
		Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body		

Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Workers	Skin contact	Long-term systemic effects	40mg/kg BW/d
Consumers	Skin contact	Long-term systemic effects	8mg/kg BW/d
Consumers	Ingestion	Long-term systemic effects	8mg/kg BW/d
Workers	Skin contact	Acute systemic effects	40mg/kg BW/d
Consumers	Skin contact	Acute systemic effects	8mg/kg BW/d
Consumers	Ingestion	Acute systemic effects	8mg/kg BW/d
Workers	Inhalation	Acute systemic effects	260 mg/m ³
Workers	Inhalation	Acute local effects	260 mg/m ³
Workers	Inhalation	Long-term systemic effects	260 mg/m ³
Workers	Inhalation	Long-term local effects	260 mg/m ³
Consumers	Inhalation	Acute systemic effects	50 mg/m ³
Consumers	Inhalation	Acute local effects	50 mg/m ³
Consumers	Inhalation	Long-term systemic effects	50 mg/m ³
Consumers	Inhalation	Long-term local effects	50 mg/m ³

Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	23.5 mg/kg
Sea water	15.4 mg/l
Fresh water	154 mg/l
Fresh water sediment	570.4 mg/kg
Onsite sewage treatment plant	100 mg/kg

8.2 Exposure controls

Personal protective equipment

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 120 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Control of environmental exposure

Prevent product from entering drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|---|---|
| a) Appearance | Form: liquid
Color: colorless |
| b) Odor | characteristic |
| c) Odor Threshold | 10 ppm |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/range: -98 °C |
| f) Initial boiling point and boiling range | 64.7 °C |
| g) Flash point | 9.7 °C - closed cup - Regulation (EC) No. 440/2008, Annex, A.9 |
| h) Evaporation rate | 6.3 - Diethyl ether 1.9 - n-butyl acetate |
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or explosive limits | Upper explosion limit: 44 %(V)
Lower explosion limit: 5.5 %(V) |
| k) Vapor pressure | 169.27 hPa at 25 °C |

l) Vapor density	1.11
m) Relative density	0.79 - 0.8 at 20 °C
n) Water solubility	1,000 g/l at 20 °C - completely miscible at 20 °C soluble
o) Partition coefficient: n-octanol/water	log Pow: -0.77 - (Lit.), Bioaccumulation is not expected.
p) Autoignition temperature	455.0 °C at 1,013 hPa - DIN 51794
q) Decomposition temperature	Distillable in an undecomposed state at normal pressure.
r) Viscosity	Viscosity, kinematic: 0.54 - 0.59 mm ² /s at 20 °C Viscosity, dynamic: > 0.544 - < 0.59 mPa.s at 25 °C
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

Minimum ignition energy	0.14 mJ
Conductivity	< 1 µS/cm
Relative vapor density	1.11

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion with:

Oxidizing agents
perchloric acid
perchlorates
salts of oxyhalogenic acids
chromium(VI) oxide
halogen oxides
nitrogen oxides
nonmetallic oxides
chromosulfuric acid
chlorates
hydrides
zinc diethyl
halogens
powdered magnesium
hydrogen peroxide
Nitric acid
sulfuric acid
permanganic acid
sodium hypochlorite
Exothermic reaction with:

acid halides
Acid anhydrides
Reducing agents
acids
Bromine
Chlorine
Chloroform
magnesium
tetrachloromethane
Risk of ignition or formation of inflammable gases or vapours with:
Fluorine
Oxides of phosphorus
Raney-nickel
Generates dangerous gases or fumes in contact with:
Alkaline earth metals
Alkali metals

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

various plastics, magnesium, zinc alloys

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity estimate Oral - 100.1 mg/kg

(Expert judgment)

Symptoms: Nausea, Vomiting

Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l

(Expert judgment)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300.1 mg/kg

(Expert judgment)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

Remarks:

(ECHA)

Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

Remarks:

(ECHA)

Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative
(OECD Test Guideline 406)

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Ames test

Salmonella typhimurium

Result: negative

In vitro mammalian cell gene mutation test

Chinese hamster lung cells

Result: negative

OECD Test Guideline 474

Mouse - male and female - Bone marrow

Result: negative

Carcinogenicity

Did not show carcinogenic effects in animal experiments.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Causes damage to organs. - Eyes, Central nervous system

Remarks:

Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Acute oral toxicity - Nausea, Vomiting

Acute inhalation toxicity - Irritation symptoms in the respiratory tract.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: PC1400000

Acute effects:, Headache, Dizziness, Drowsiness, narcosis, Blindness, Impairment of vision, irritant effects, Nausea, Vomiting, agitation, spasms, inebriation, Coma

Drying-out effect resulting in rough and chapped skin.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

acidosis

drop in blood pressure

agitation, spasms

inebriation

Dizziness

Drowsiness

Headache

Impairment of vision

Blindness

narcosis

Coma

Symptoms may be delayed.

Damage to:

Liver
Kidney
Cardiac
Irreversible damage of the optical nerve.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	flow-through test LC50 - <i>Lepomis macrochirus</i> (Bluegill) - 15,400.0 mg/l - 96 h (US-EPA)
Toxicity to daphnia and other aquatic invertebrates	semi-static test EC50 - <i>Daphnia magna</i> (Water flea) - 18,260 mg/l - 96 h (OECD Test Guideline 202)
Toxicity to algae	static test ErC50 - <i>Pseudokirchneriella subcapitata</i> (green algae) - ca. 22,000.0 mg/l - 96 h (OECD Test Guideline 201)
Toxicity to bacteria	static test IC50 - activated sludge - > 1,000 mg/l - 3 h (OECD Test Guideline 209)

12.2 Persistence and degradability

Biodegradability	Result: 99 % - Readily biodegradable. (OECD Test Guideline 301D)
Biochemical Oxygen Demand (BOD)	600 - 1,120 mg/g Remarks: (IUCLID)
Chemical Oxygen Demand (COD)	1,420 mg/g Remarks: (IUCLID)
Theoretical oxygen demand	1,500 mg/g Remarks: (Lit.)
Ratio BOD/ThBOD	76 % Remarks: Closed Bottle test(IUCLID)

12.3 Bioaccumulative potential

Bioaccumulation	<i>Cyprinus carpio</i> (Carp) - 72 d at 20 °C - 5 mg/l(Methanol)
	Bioconcentration factor (BCF): 1.0

12.4 Mobility in soil

Will not adsorb on soil.

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological information Avoid release to the environment.

Stability in water at 19 °C 83 - 91 % - 72 h
Remarks: Hydrolyzes on contact with water. Hydrolyzes readily.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1230 IMDG: 1230 IATA: 1230

14.2 UN proper shipping name

ADR/RID: METHANOL
IMDG: METHANOL
IATA: Methanol

14.3 Transport hazard class(es)

ADR/RID: 3 (6.1) IMDG: 3 (6.1) IATA: 3 (6.1)

14.4 Packaging group

ADR/RID: II IMDG: II IATA: II

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Authorisations and/or restrictions on use

REACH - Restrictions on the manufacture, : Methanol
placing on the market and use of certain
dangerous substances, preparations and articles
(Annex XVII)

National legislation

Seveso III: Directive 2012/18/EU of the : ACUTE TOXIC

European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

: FLAMMABLE LIQUIDS

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapor.
H301	Toxic if swallowed.
H301 + H311 + H331	Toxic if swallowed, in contact with skin or if inhaled.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs (/\$/*_ORGAN_SINGLE\$/).
H371	May cause damage to organs.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Annex: Exposure scenario

Identified uses:

Use: Used as chemical intermediate

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 3, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals
PC19: Intermediate
PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC15: Use as laboratory reagent
ERC1, ERC4, ERC6a: Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in manufacture of another substance (use of intermediates)

Use: Formulation of preparations

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 10: Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)
PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC15: Use as laboratory reagent
ERC2: Formulation of preparations

Use: Industrial use of processing aids in processes and products, not becoming part of articles

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 3, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals
PC20: Products such as pH-regulators, flocculants, precipitants, neutralization agents PC21: Laboratory chemicals
PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC15: Use as laboratory reagent
ERC4, ERC6b: Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use of reactive processing aids

Use: Used as laboratory reagent.

SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU 3, SU 22, SU24: Industrial uses: Uses of substances as such or in preparations at industrial sites, Professional uses: Public domain (administration, education, entertainment, services, craftsmen), Scientific research and development
PC19: Intermediate
PC20: Products such as pH-regulators, flocculants, precipitants, neutralization agents
PC21: Laboratory chemicals
PROC10: Roller application or brushing
PROC15: Use as laboratory reagent
ERC4, ERC6a, ERC6b: Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in manufacture of another substance (use of intermediates), Industrial use of reactive processing aids

Use: Surface treatment

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 3, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals
PC35: Washing and cleaning products (including solvent based products)
PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)
PROC7: Industrial spraying
PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities
PROC10: Roller application or brushing
PROC13: Treatment of articles by dipping and pouring
ERC2, ERC4, ERC6a: Formulation of preparations, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in manufacture of another substance (use of intermediates)

1. Short title of Exposure Scenario: Used as chemical intermediate

Main User Groups	: SU 3
Sectors of end-use	: SU 3, SU9
Chemical product category	: PC19
Process categories	: PROC1, PROC2, PROC3, PROC4, PROC8b, PROC15

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: **ERC1, ERC4, ERC6a**

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: **PROC1, PROC2, PROC3, PROC4, PROC8b, PROC15, PC19**

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

Physical Form (at time of use) : High volatile liquid

Frequency and duration of use

Application duration : > 4 h

Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Use only in area provided with appropriate exhaust ventilation., Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC1	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.00686 mg/kg BW/d	0
PROC1	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	0.0133 mg/m ³	0
PROC2	ECETOC TRA	With Local Exhaust	Dermal	0.274 mg/kg BW/d	0.007

		Ventilation			
PROC2	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	3.33 mg/m ³	0.013
PROC3	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	6.67 mg/m ³	0.026
PROC3	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.137 mg/kg BW/d	0.003
PROC4	ECETOC TRA	With Local Exhaust Ventilation	Dermal	1.37 mg/kg BW/d	0.034
PROC4	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	13.3 mg/m ³	0.051
PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	10 mg/m ³	0.038
PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Dermal	2.74 mg/kg BW/d	0.069
PROC15	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.0686 mg/kg BW/d	0.002
PROC15	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	13.3 mg/m ³	0.051

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Formulation of preparations

Main User Groups : **SU 3**
 Sectors of end-use : **SU 10**
 Process categories : **PROC2, PROC3, PROC4, PROC8b, PROC9, PROC15**
 Environmental Release Categories : **ERC2:**

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC2

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC2, PROC3, PROC4, PROC8b, PROC9, PROC15

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use) : High volatile liquid

Frequency and duration of use

Application duration : > 4 h
Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Use only in area provided with appropriate exhaust ventilation., Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC2	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	3.33 mg/m ³	0.013
PROC2	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.274 mg/kg BW/d	0.007
PROC3	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	6.67 mg/m ³	0.026
PROC3	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.137 mg/kg BW/d	0.003
PROC4	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	13.3 mg/m ³	0.051
PROC4	ECETOC TRA	With Local Exhaust	Dermal	1.37 mg/kg BW/d	0.034

		Ventilation			
PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	10 mg/m ³	0.038
PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Dermal	2.74 mg/kg BW/d	0.069
PROC9	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	26.7 mg/m ³	0.103
PROC9	ECETOC TRA	With Local Exhaust Ventilation	Dermal	1.37 mg/kg BW/d	0.034
PROC15	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.0686 mg/kg BW/d	0.002
PROC15	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	13.3 mg/m ³	0.051

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Industrial use of processing aids in processes and products, not becoming part of articles

Main User Groups : **SU 3**
 Sectors of end-use : **SU 3, SU9**
 Chemical product category : **PC20, PC21**
 Process categories : **PROC1, PROC2, PROC3, PROC4, PROC8b, PROC9, PROC10, PROC15**
 Environmental Release Categories : **ERC4, ERC6b:**

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC4, ERC6b

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8b, PROC9, PROC10, PROC15, PC20, PC21

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
 Physical Form (at time of use) : High volatile liquid

Frequency and duration of use

Application duration : > 4 h
 Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Use only in area provided with appropriate exhaust ventilation., Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source**Environment**

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC1	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.00686 mg/kg BW/d	0
PROC1	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	0.0133 mg/m ³	0
PROC2	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	3.33 mg/m ³	0.013
PROC2	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.274 mg/kg BW/d	0.007
PROC3	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.137 mg/kg BW/d	0.003
PROC3	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	6.67 mg/m ³	0.026
PROC4	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	13.3 mg/m ³	0.051
PROC4	ECETOC TRA	With Local Exhaust Ventilation	Dermal	1.37 mg/kg BW/d	0.034

PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Dermal	2.74 mg/kg BW/d	0.069
PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	10 mg/m ³	0.038
PROC9	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	26.7 mg/m ³	0.103
PROC9	ECETOC TRA	With Local Exhaust Ventilation	Dermal	1.37 mg/kg BW/d	0.034
PROC10	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	33.3 mg/m ³	0.128
PROC10	ECETOC TRA	With Local Exhaust Ventilation	Dermal	5.49 mg/kg BW/d	0.137
PROC15	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.0686 mg/kg BW/d	0.002
PROC15	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	13.3 mg/m ³	0.051

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Used as laboratory reagent.

Main User Groups : **SU 22**
 Sectors of end-use : **SU 3, SU 22, SU24**
 Chemical product category : **PC19, PC20, PC21**
 Process categories : **PROC10, PROC15**
 Environmental Release Categories : **ERC4, ERC6a, ERC6b:**

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC4, ERC6a, ERC6b

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC10, PROC15, PC19, PC20, PC21

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

Physical Form (at time of use) : High volatile liquid

Frequency and duration of use

Application duration : > 4 h

Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Use only in area provided with appropriate exhaust ventilation., Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC10	ECETOC TRA	With Local Exhaust Ventilation	Dermal	5.49 mg/kg BW/d	0.137
PROC10	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	33.3 mg/m ³	0.128
PROC15	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.0686 mg/kg BW/d	0.002
PROC15	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	13.3 mg/m ³	0.051

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Surface treatment

Main User Groups : **SU 3**
Sectors of end-use : **SU 3, SU9**
Chemical product category : **PC35**
Process categories : **PROC5, PROC7, PROC8a, PROC10, PROC13**
Environmental Release Categories : **ERC2, ERC4, ERC6a:**

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC2, ERC4, ERC6a

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC5, PROC7, PROC8a, PROC10, PROC13, PC35

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use) : High volatile liquid

Frequency and duration of use

Application duration : > 4 h
Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Use only in area provided with appropriate exhaust ventilation., Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment	Specific conditions	Value	Level of Exposure	RCR*
-----------------------	---------------------	---------------------	-------	-------------------	------

	Method				
PROC5	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	33.3 mg/m ³	0.128
PROC5	ECETOC TRA	With Local Exhaust Ventilation	Dermal	2.74 mg/kg BW/d	0.069
PROC7	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	33.3 mg/m ³	0.128
PROC7	ECETOC TRA	With Local Exhaust Ventilation	Dermal	8.57 mg/kg BW/d	0.214
PROC8a	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	33.3 mg/m ³	0.128
PROC8a	ECETOC TRA	With Local Exhaust Ventilation	Dermal	2.74 mg/kg BW/d	0.069
PROC10	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	33.3 mg/m ³	0.128
PROC10	ECETOC TRA	With Local Exhaust Ventilation	Dermal	5.49 mg/kg BW/d	0.137
PROC13	ECETOC TRA	With Local Exhaust Ventilation	Dermal	2.74 mg/kg BW/d	0.069
PROC13	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	33.3 mg/m ³	0.128

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).