

Dichiarazione di Conformità **Declaration of Conformity**

FACI s.a.s

VIA PADRE U. FRASCA s.n.c.
66013 CHIETI SCALO (CH) - ITALIA

Dichiara che:

le caldaie modello FILTROASPIRATA sono della stessa gamma della precedente versione FACI

Declares that:

the FILTROASPIRATA model boilers have the same range of the previous version FACI

Attenersi alle Direttive Europee:

Direttiva bassa tensione 2006/95/CE

Direttiva EMC 2004/108/CE

2006/42/CEE (aggiornata con la direttiva CE 93/68/CEE e con la direttiva prodotti da costruzione 89/106/CEE)

Direttiva macchine 2006/49/CE ai sensi della parte A dell'all. II.

Comply with European Directives:

Low voltage directive 2006/95/CE

EMC directive 2004/108/CE

2006/42/CEE (amended by CE directive 93/68/CEE and by construction products directive 89/106/CEE)

Machinery directive 2006/49/CE as part A of the annex II.

PROVE FACI secondo EN 303-5 2004.

Combustibile - p.c.i.

Pellet di legna (L=2-3 cm, diametro=6mm, umidità=4,3%)

Hi= 18230 kJ/kg

MODELLO FILTROASPIRATA		26	34	51	super 3C 85	super 3C 135	super 3C 225
P.C.I. pellet 2,5cm d.6mm U=4,3%	kJ/kg	18230	18230	18230	18230	18230	18230
Potenza focolare	kW	26,6	34,9	51	85	135	225
Portata combustibile	kg/h	5,25	6,89	12,64	14,40	22,81	41,08
Potenza combustione	kW	23,9	32,0	57,7	70,3	104,1	187,5
rendimento di combustione	%	89,8	91,7	90,2	90,1	90,1	90,1
Potenza utile	kW	23,1	30,7	47	78	115	199
Rendimento all'acqua	%	86,8	88,0	87,5	86,4	88,3	89,4
Temperatura fumi	°C	186	195,0	190	189	190	190
Depressione camino	Pa	3	8,1	12	20	25	25
O2	%	10,0	10,0	10,0	10,0	10,0	10,0
CO	mg/m3	630	810	786	760	630	550
OGC	mg/m3	31	33	34	34	35	35
Polveri	mg/m3	21	24	25	25	26	26
NOx	mg/m3	110	122	131	133	142	151

CHIETI SCALO 14/01/2016

FACI s.a.s
di V. Matricciani & C.