



			2-Pipe ECOi EX ME2 Series High Efficiency 8-64HP U-8ME2E8	2-Pipe ECOi EX ME2 Series High Efficiency 8-64HP U-10ME2E8	2-Pipe ECOi EX ME2 Series High Efficiency 8-64HP U-12ME2E8	2-Pipe ECOi EX ME2 Series High Efficiency 8-64HP U-14ME2E8	2-Pipe ECOi EX ME2 Series High Efficiency 8-64HP U-16ME2E8	2-Pipe ECOi EX ME2 Series High Efficiency 8-64HP U-18ME2E8	2-Pipe ECOi EX ME2 Series High Efficiency 8-64HP U-20ME2E8
Cooling Capacity		kW	22,4	28,0	33,5	40,0	45,0		56,0
EER		W/W	4,70	4,37	3,96	3,88	3,52	4,55	4,38
Heating Capacity		kW	25,0		37,5	45,0	50,0	56,0	
COP		W/W	5,13		4,73	4,56	4,42		4,77
Power Source		V	380 / 400 / 415		380 / 400 / 415	380 / 400 / 415	380 / 400 / 415		380 / 400 / 415
Dimensions	H x W x D	mm	1.842 x 770 x 1.000		1.842 x 1.180 x 1.000	1.842 x 1.180 x 1.000	1.842 x 1.180 x 1.000		1.842 x 1.600 x 1.000
Net Weight		kg	210	210	270	315	315	420	420
Operating Range	Cooling Min. - Max.	°C	-10 ~ +52	-10 ~ +52	-10 ~ +52	-10 ~ +52	-10 ~ +52	-10 ~ +52	-10 ~ +52
Operating Range	Heating Min. - Max.	°C	-25 ~ +18	-25 ~ +18	-25 ~ +18	-25 ~ +18	-25 ~ +18	-25 ~ +18	-25 ~ +18
Sound Pressure Level	Normal mode	dB (A)	54,0	56,0	59,0	60,0	61,0	58,5	59,0
Sound Pressure Level	Silent mode	dB (A)	51,0	53,0	56,0	57,0	58,0	55,5	56,0
Refrigerant (R410A) / CO2 Eq.		kg / T	5,6 / 11,6928	5,6 / 11,6928	8,3 / 17,3304	8,3 / 17,3304	8,3 / 17,3304		11,2 / 23,3856