

B03.C

Canon
SEE IMPOSSIBLE

imageRUNNER
ADVANCE
C5560i / C5550i
C5540i / C5535i

PRODUCT SPECIFICATIONS



Main Unit

Type

Color Laser Multifunctional

Core Functions

Standard: Print, Copy, Scan, Send, Store
Optional: Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

Memory

4.0 GB RAM

Hard Disk Drive

Standard: 250 GB
Maximum: 1 TB

Mirroring Hard Disk Drive

Optional: 250 GB, 1 TB
Method: Raid1

Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T
Wireless LAN (IEEE 802.11 b/g/n)

Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),
USB 2.0 x1 (Device)
Optional: Serial Interface, Copy Control Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets
Maximum: 6,350 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes,
100-sheet Stack Bypass

Optional: Dual 550-sheet Paper Cassettes
(CASSETTE FEEDING UNIT-AM1),
2,450-sheet High-Capacity Paper
Cassette (HIGH CAPACITY CASSETTE
FEEDING UNIT-A1), 2,700-sheet Paper
Deck (PAPER DECK UNIT-F1)

Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets
Maximum: 3,450 Sheets
(with External Finisher and Copy Tray)

Finishing Capabilities

Standard: Collate, Group
With Inner Finisher: Collate, Group, Offset, Staple, Hole Punch,
Staple-Free Staple, Staple On Demand
With External Finishers: Collate, Group, Offset, Staple, Booklet, Hole
Punch, Staple-Free Staple, Staple On Demand

Supported Media Types

Paper: Thin, Plain, Recycled, Color, Heavy,
Cassettes: Pre-punched, Letterhead, Bond,
(1/2) Transparency, Tab, Envelope

Stack Bypass: Thin, Plain, Recycled, Color, Heavy,
Pre-punched, Labels, Letterhead,
Bond, Coated, Transparency, Tab,
Tracing, Envelope

CASSETTE FEEDING UNIT-AM1

Thin, Plain, Recycled, Color, Heavy, Pre-punched,
Letterhead, Bond, Transparency

HIGH CAPACITY CASSETTE FEEDING UNIT-A1

Thin, Plain, Recycled, Color, Heavy, Pre-punched,
Letterhead, Bond

PAPER DECK UNIT-F1

Thin, Plain, Recycled, Color, Heavy, Pre-punched,
Letterhead, Bond

Supported Media Sizes

Paper: Letter, Executive, Statement-R, Envelope
Cassette 1: [No.10 (COM10), DL, ISO-C5], Custom Size
(3-7/8" x 5-7/8" to 11-3/4" x 8-1/2")

Paper: 12" x 18", 11" x 17", Legal, Letter, Letter-R,
Cassette 2: Executive, Statement-R, Envelope [No.10
(COM10), Monarch, DL, ISO-C5], Custom
Size (3-7/8" x 7-1/8" to 12" x 18")

Stack Bypass

12" x 18", 11" x 17", Legal, Letter, Letter-R,
Executive, Statement, Statement-R,
Envelope [No.10 (COM10), Monarch,
DL, ISO-C5], Envelope Custom Size
(3-7/8" x 3-7/8" to 12-5/8" x 18"),
Custom Size (3-7/8" x 5-1/2" to
12-5/8" x 18"), Free Size (3-7/8" x 5-1/2"
to 12-5/8" x 18")



0.028

CASSETTE FEEDING UNIT-AM1

12" x 18" 11" x 17" Legal, Letter, Letter-R, Executive, Statement-R, Custom Size (3-7/8" x 7-1/8" to 12" x 18")
HIGH CAPACITY CASSETTE FEEDING UNIT-A1 Letter
PAPER DECK UNIT-F1 Letter

Supported Media Weights

Cassettes 14 lb Bond to 40 lb Index (52 to 256 g/m²)
Stack Bypass 14 lb Bond to 10 lb Cover (52 to 300 g/m²)
Duplexing 14 lb Bond to 80 lb Cover (52 to 220 g/m²)

Warm-up Time

From Power On 30 Seconds
From Sleep Mode 10 Seconds
Quick Startup Mode 4 Seconds

Dimensions (W x D x H)

24-3/8" x 29-1/4" x 37-3/8" (620 mm x 742 mm x 950 mm)*

Installation Space (W x D)

Basic Stack Bypass + Cassette drawers open
37-1/8" x 46-3/8" (943 mm x 1,176 mm)*

Weight

Approx. 313 lb (142 kg)*

Print Specifications

Print Speed (BW and Color)

iR ADV Up to 60 ppm (Letter), Up to 36 ppm
C5560i (Letter-R), Up to 34 ppm (Legal),
Up to 32 ppm (11" x 17")

iR ADV Up to 50 ppm (Letter), Up to 30 ppm
C5550i (Letter-R), Up to 29 ppm (Legal),
Up to 27 ppm (11" x 17")

iR ADV Up to 40 ppm (Letter), Up to 24 ppm
C5540i (Letter-R), Up to 23 ppm (Legal),
Up to 22 ppm (11" x 17")

iR ADV Up to 35 ppm (Letter), Up to 23 ppm
C5535i (Letter-R), Up to 21 ppm (Legal),
Up to 18 ppm (11" x 17")

Print Resolution

1200 dpi x 1200 dpi, 600 dpi x 600 dpi

Standard Page Description Languages

UFR II, PCL 5, Adobe® PS 3

Direct Print

Available from USB, Advanced Box Remote UI,
and Web Access

Supported File Types

PDF, TIFF, JPEG, EPS, XPS

Printing from Mobile Devices and Cloud-based Services

A range of software and MFP-based solutions are
available to provide printing from mobile devices or
Internet-connected devices and cloud-based services
depending on your requirements.

Fonts

PCL fonts 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andale Mono, WT 1, K/5/T (Japanese,
Korean, Simplified and Traditional
Chinese), Barcode Fonts*

PS fonts 136 Roman

Operating System*

UFR II Server 2003/Server 2003 R2/Windows
Vista*/Server 2008/Windows 7/Server
2008 R2/Windows 8/Server 2012/
Windows 8.1/Server 2012 R2/Windows
10, MAC OS X (10.6.8 or later)

PCL Server 2003/Server 2003 R2/Windows
Vista*/Server 2008/Windows 7/Server
2008 R2/Windows 8/Server 2012/
Windows 8.1/Server 2012 R2/Windows 10

PS Server 2003/Server 2003 R2/Windows
Vista*/Server 2008/Windows 7/Server
2008 R2/Windows 8/Server 2012/
Windows 8.1/Server 2012 R2/Windows
10, MAC OS X (10.6.8 or later)

Print Features

Suspend/Job Timeout, Subset Finishing (PS only),
Profile Settings, Secure Print, Forced Hold Printing,
Watermark, Page Border, Header/Footer, Page Layout,
Two-sided Printing, Collating, Booklet Printing, Grouping,
Mixed Paper Sizes/Orientations, Off-setting, Printing on
Transparencies, Front/Back Covers, Toner Reduction,
Poster Printing

Copy Specifications

Copy Speed (BW and Color)

iR ADV Up to 60 ppm (Letter), Up to 36 ppm
C5560i (Letter-R), Up to 34 ppm (Legal),
Up to 32 ppm (11" x 17")

iR ADV Up to 50 ppm (Letter), Up to 30 ppm
C5550i (Letter-R), Up to 29 ppm (Legal),
Up to 27 ppm (11" x 17")

iR ADV Up to 40 ppm (Letter), Up to 24 ppm
C5540i (Letter-R), Up to 23 ppm (Legal),
Up to 22 ppm (11" x 17")

iR ADV Up to 35 ppm (Letter), Up to 23 ppm
C5535i (Letter-R), Up to 21 ppm (Legal),
Up to 18 ppm (11" x 17")

First-Copy-Out Time (Letter)

iR ADV As fast as 2.9 seconds (BW)/
C5560i 4.5 seconds (Color)

iR ADV As fast as 3.5 seconds (BW)/
C5550i 5.2 seconds (Color)

iR ADV As fast as 4.1 seconds (BW)/
C5540i 6.1 seconds (Color)

iR ADV As fast as 4.9 seconds (BW)/
C5535i 7.4 seconds (Color)

Copy Resolution

Reading 600 dpi x 600 dpi

Printing 1200 dpi x 1200 dpi

Multiple Copies

Up to 9,999 copies

Copy Exposure

Automatic or Manual (9 Levels)

Magnification

25%-400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements

129%, 129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper
Setting, Previous Settings, Favorite Settings, Finishing,
Two-Sided, Density Adjustment, Original Type Selection,
Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Book to Two Pages, Two-sided Original, Finishing,
Booklet, Job Build, Non 1, Add Cover, Insert Sheets,
Different Size Originals, Density Adjustment, Original
Type Selection, Transparency Cover/Sheets, Page
Numbering, Copy Set Numbering, Sharpness, Erase
Frame, Secure Watermark, Print Date, Shift, Gutter
Print & Check, Negative/Positive, Repeat Images, Merge
Job Blocks, Job Done Notice, Mirror Image, Print on Tab,
Store in Mail Box, Superimpose Image, Copy ID Card,
Detect Feeder Multi-Sheet Feed, Free Size Original, Color
Balance, Adjust One-Touch Color, Area Designation

Scan Specifications

Type

Color Platen and Single-pass Duplexing Automatic
Document Feeder

Document Feeder Paper Capacity

150 Sheets (20 lb Bond)

Document Feeder Supported Media Sizes

11" x 17" Legal, Letter, Letter-R, Statement, Statement-R

Document Feeder Supported Media Weights

BW Original 13 lb Bond to 58 lb Cover (50 to 157 g/m²)

CL Original 17 lb Bond to 58 lb Cover (64 to 157 g/m²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects (Up to 4.4 lb (2 kg))

Pull Scan

Color Network ScanGear2 for both TWAIN and JVA

Supported Windows Vista*/7/8/8.1/10
OS Windows Server 2003/Server 2003 R2/
Server 2008/Server 2008 R2/Server
2012/Server 2012 R2

Scan Resolution

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi,

200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100 dpi

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to
mobile devices and cloud-based services depending on
your requirements.

Scan Speed (Letter)

Single-sided Scanning (BW)

80 ppm (300 dpi)/80 ppm (600 dpi)

Single-sided Scanning (Color)

80 ppm (300 dpi)/60 ppm (600 dpi)

Double-sided Scanning (BW)

160 ppm (300 dpi)/150 ppm (600 dpi)

Double-sided Scanning (Color)

160 ppm (300 dpi)/90 ppm (600 dpi)

Send Specifications

Destination

E-mail/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail
Box, Super G3 Fax (Optional), IP Fax (Optional)

Color Mode

Automatic-Color Select (Full Color/Grayscale),
Automatic-Color Select (Full Color/Black-and-White),
Full color, Grayscale, and Black-and-White

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Send Resolution

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400
dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi,
100 x 100 dpi

Communication Protocol

File FTP, SMB, WebDAV

E-mail/1-Fax SMTP, POP3, 1-Fax (Simple, Full)

File Format

Standard TIFF, JPEG, PDF (Compact, Searchable,
Apply policy, Optimize for Web, PDF
4/1-b), XPS (Compact, Searchable),
Office Open XML (PowerPoint®, Word)

Optional PDF (Trace & Smooth, Encrypted),
PDF/xPS (Digital Signature)

Universal Send Features

Original Type Selection, Two-sided Original, Book to Two
Pages, Different-size Originals, Density Adjustment,
Sharpness, Copy Ratio, Erase Frame, Job Build, Direct
Send, Delayed Send, Preview, Job Done Notice, File Name,
Subject/Message, Reply-to, E-mail Priority, TX Report,
Original Content Orientation, Skip Blank Originals, Detect
Feeder Multi-Sheet Feed

Fax Specifications

Maximum Number of Connection Lines

4

Modem Speed

Super G3 33.6 kbps
G3 14.4 kbps

Compression Method

M= MMR, MMR, BIG

Resolution

400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi

Sending/Recording Size

statement-R to T¹ x 1¹

Fax Memory

Up to 30,000 pages

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 dials

Sequential Broadcast

Max. 250 addresses

Memory Backup

yes

Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Built, Specifying the Sender's Name (when sending fax), Sender's Name (T¹), Select Line, Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder, Multi-Sheet Feeder

Store Specifications

Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV

Supported Client PC

Windows (Windows Vista/7/8/8.1/10)

Concurrent Connections (Max.)

SMB 64

WebDAV 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD)

Approx. 480 GB (1 TB HDD)

Advanced Box Features:

Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Login, Search Function, Scan Function, Printing a PDF File with a Password, ImageWARE, Secure Audit Manager, Support

Memory Media

Standard: USB

Security Specifications

Authentication

Standard: Universal Login Manager, User Authentication, Department ID Authentication, Access Management System, Device and Function Level Login
Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated)

Optional

Hard Disk Drive Monitoring, Hard Disk Drive removal, IEEE 2500.2 Common Criteria Certification, Data Loss Preventions (Requires uniFLOW)

Network

Standard: IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP v3, IEEE 802.1x, IPv6, SMTP Authentication, POP Authentication, before SMTP

Document

Standard: Secure Print, Adobe Lifecycle Rights Management, ES2 Integration
Optional: Encrypted PDF, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scrambling

Environmental Specifications

Operating Environment

Temperature: 50 to 65 °F
Humidity: 20 to 80 % RH (no condensation)

Power Requirements

C5560/C5550: 120-27V AC, 60 Hz, 1.5 A
C5540/C5535: 120-27V AC, 60 Hz, 1.0 A

Plug (Main Unit)

C5560/C5550: NEMA 3-20P
C5540/C5535: NEMA 3-15P

Power Consumption

Maximum: Approx. 1.8 kW
Standby: Approx. 66.2 W
Sleep Mode: Approx. 3.8 W
Typical Electricity Consumption (TRC) Rating
3.2 kWh (R ADV C5560)
2.5 kWh (R ADV C5550)
2.0 kWh (R ADV C5540)
1.6 kWh (R ADV C5535)

Standards

ENERGY STAR[®] Certified
Rated EPEAT[®] Gold
RoHS Compliant

Consumables

Toner

GPR-55 Toner[®]

Toner Yield (Estimated @ 6% Coverage)

Black: 89,000 images
Color (CMY): 19,600 images

Fiery Print Controller Specifications (Optional)

ColorPASS-GX500 (External)

(R ADV C5560/R ADV C5550) only

System

Fiery F5200 Pro

Print Resolution

200 dpi x 1200 dpi, 600 dpi x 600 dpi

Standard Page Description Languages

Adobe PS 3, PCL 5 (Driver-less)

Memory

4 GB

Hard Disk Drive

1 TB

Processor

Intel Core i5-4570S 2.9 GHz up to 3.6 GHz w/ Turbo

Fonts

PS: 138 Adobe PS Fonts

PCL: 113 PCL Fonts

Supported Operating Systems

Windows Vista (32 and 64 bit), Windows 7 (32 and 64 bit), Windows 8 (32 and 64 bit), Windows 8.1 (32 and 64 bit), Windows 10 (32 and 64 bit), Windows Server 2008 (32 and 64 bit), Windows Server 2008 R2 (64 bit only), Windows Server 2012 (64 bit only), Windows Server 2012 R2 (64 bit only), MAC OS (10.7, 10.8, 10.9, 10.10, 10.11)

Interface

2 x Ethernet (100Base-T/100Base-T⁴/10Base-T), USB 3.0 x 6 (Front x 2, Rear x 4), USB 2.0 x 2 (Front x 2)

Network Protocols

TCPIP (LPR, Port 9100), SNMP (RRP, HTTP, HTTPS, FIP), SMB, DNS

Direct Print

PDF, TAPPE3, EPS, TIFF, JDF 1.4/JMF

VDP

FreeForm2 - PDF/VT-2, PPM, 3, VPS

Fiery Print Controller Standard Features

Fiery HDI FOLDERS, Virtual Printers, Unity Display (Monitor required), Fiery Job Fiery COMMAND, JDR45 ACTION 5, Paper Catalog, Fiery SPD/IDV, Fiery REMOTE SCAN

Fiery Print Controller Options

Fiery IMPOSE, Fiery COMPPOSE, Fiery IMPOSE AND COMPPOSE, Graphix Arts Package Premium Sheet Activate/Removable HDD Kit (BI/Integration Interface), app Stand (9" display, keyboard and mouse)

Dimensions (W x D x H)

9-1/2" x 19" x 19-1/8" (215 mm x 483 mm x 485 mm)

imagePASS-P1 (Embedded)

System

Fiery F5200

Print Resolution

200 dpi x 1200 dpi, 600 dpi x 600 dpi

Standard Page Description Languages

PCL6, Adobe PS 3

Memory

2 GB

Hard Disk Drive

500 GB

Processor

Intel Celeron G 820 2.7 GHz

Fonts

PS: 138 Adobe PS Fonts

PCL: 113 PCL Fonts

Supported Operating Systems

Windows Vista (32 and 64 bit), Windows 7 (32 and 64 bit), Windows 8 (32 and 64 bit), Windows 8.1 (32 and 64 bit), Windows Server 2008 (32 and 64 bit), Windows Server 2008 R2 (64 bit only), Windows Server 2012 (64 bit only), Windows Server 2012 R2 (64 bit only), MAC OS (10.7 or higher)

Interface

2 x Ethernet (1000Base-T/1000Base-TX/10Base-T),
USB x 3 (0 x 2 (Rear x 2), USB x 2 (0 x 4 (Rear x 4))

Network Protocols

TCP/IP (LPR/Port 9100/PPS/SMB/FTP)/DNS

Fiery Print Controller Features

FIERY COMMAND WORKSTATION 5, PAPER CATALOG,
FIERY SPOT ON, FIERY REMOTE SCAN

Fiery Print Controller Options

FIERY IMPOSE, FIERY COMPOSE, FIERY IMPOSE AND
COMPOSE, Productivity package, Web activate (Includes
Fiery .DF), Hot Folders License

Dimensions (W x D x H)

11-1/4" x 3-5/8" x 11-5/8" (285 mm x 93 mm x 295 mm)

Paper Supply Options

CASSETTE FEEDING UNIT-AM1

Paper 550 Sheets x 2 Cassettes
Capacity 120 lb. Bond (80 g/m²)
Paper Size 12" x 18" (11" x 17" Legal, Letter, Letter-R,
Executive, Statement-R, and Custom Size
(3-7/8" x 7-1/8" to 12" x 8"
(98.0 x 82.0 to 304.8 x 457.2 mm))

Paper Weight 14 lb. Bond to 140 lb. Index
(52 to 256 g/m²)

Power Source From the Main Unit

Dimensions (W x D x H) 24-3/8" x 27-5/8" x 9-7/8"

(620 mm x 700 mm x 251 mm)

Weight Approx. 49.6 lb. (22.5 kg)

HIGH-CAPACITY CASSETTE FEEDING UNIT-A1

Paper 2,450 sheets (20 lb. Bond (80 g/m²))

Capacity

Paper Size Letter

Paper Weight 14 lb. Bond to 140 lb. Index
(52 to 256 g/m²)

Power Source From the Main Unit

Dimensions (W x D x H) 24-3/8" x 27-5/8" x 9-7/8"

(620 mm x 700 mm x 251 mm)

Weight 66.1 lb. (30 kg)

PAPER DECK UNIT-F1

Paper 2,700 Sheets (20 lb. Bond (80 g/m²))

Capacity

Paper Size Letter

Paper Weight 14 lb. Bond to 140 lb. Index
(52 to 256 g/m²)

Power Source From the Main Unit

Dimensions (W x D x H) 15-3/4" x 24-7/8" x 17-3/8"

(400 mm x 630 mm x 440 mm)

Weight 58.3 lb. (31 kg)

Output Options

INNER 2-WAY TRAY-J1

Number of

Trays 2

Total Output

Capacity Upper Tray 100 Sheets

Lower Tray 250 Sheets

Paper Weight 14 lb. Bond to 110 lb. Cover
(52 to 300 g/m²)

Paper Size Standard size (12" x 18", 11" x 17", Legal,
Letter, Letter-R, Executive, Statement,
Statement-R, Envelope (No 10 (COM10),
Monarch, DL, ISO-C5), Envelope Custom Size
(3-7/8" x 3-7/8" to 12-5/8" x 18")

Custom Size (3-1/8" x 3-1/2" to 12-5/8" x 18")

Dimensions (W x D x H) 16-7/8" x 16" x 8"

(427 mm x 407 mm x 176 mm)

Weight Approx. 1.3 lb. (0.6 kg)

INNER FINISHER-H1

Number of

Trays 2

Top Tray Letter/Statement/Statement-R/
Capacity Executive (45 Sheets), 12" x 18"/11" x 17"/
Legal/Letter-R (45 Sheets)

Lower Tray Letter/Statement/Statement-R/
Capacity Executive (500 Sheets), 12" x 18"/11" x 17"/
Legal/Letter-R (250 Sheets)

Paper Weight 14 lb. Bond to 110 lb. Index
(52 to 300 g/m²)

Acceptable Paper Weight 14 lb. Bond to 140 lb. Cover
(52 to 256 g/m²)

Staple Position Corner, Double

Staple Capacity Corner Staple and Double Staple

Letter/
Executive 50 Sheets (14 to 24 lb. Bond)

11" x 17"/
Legal/
Letter-R 30 Sheets (14 to 24 lb. Bond)

Staple-Free Staple
11" x 17/ 5 Sheets (14 to 17 lb. Bond)

Letter 4 Sheets (17.3 to 21.7 lb. Bond)

3 Sheets (21.7 to 28 lb. Bond)

Staple On Demand 40 Sheets (20 lb. Bond (80 g/m²))

Power Source From the Main Unit

Dimensions (W x D x H) 29-1/4" x 29-1/4" x 8-7/8"

(743 mm x 742 mm x 225 mm)

Weight Approx. 19 lb. (8.6 kg)

STAPLE FINISHER-Y1 (External)

Number of

Trays 2

Top Tray Letter/Executive/Statement/
Capacity Statement-R (3,000 Sheets), 12" x 18"/11"
x 17"/Legal/Letter-R (1,500 Sheets)

Lower Tray Letter/Executive/Statement/
Capacity Statement-R (250 Sheets), 12" x 18"/11"
x 17"/Legal/Letter-R (125 Sheets)

Paper Weight 14 lb. Bond to 140 lb. Index
(52 to 256 g/m²)

Lower Tray 14 lb. Bond to 110 lb. Cover
(52 to 300 g/m²)

Staple Position Corner, Double

Staple Capacity Corner Staple and Double Staple

Letter/
Executive 50 Sheets (24 lb. Bond (90 g/m²))

11" x 17/
Legal/
Letter-R 30 Sheets (24 lb. Bond (90 g/m²))

Staple-Free Staple
11" x 17/ 5 Sheets (14 to 17 lb. Bond (52 to 64 g/m²))

Letter 4 Sheets (17.3 to 21.7 lb. Bond (65 to 81.4 g/m²))

3 Sheets (21.7 to 28 lb. Bond (81.5 to 105 g/m²))

Staple On Demand 50 Sheets (24 lb. Bond (90 g/m²))

Power Source From the Main Unit

Dimensions 25-1/8" x 24-1/2" x 45"

(W x D x H) (637 mm x 623 mm x 1142 mm)

Weight Approx. 68.3 lb. (31 kg)

BOOKLET FINISHER-Y1 (External)

Number of

Trays 3

Top Tray Letter/Executive/Statement/
Capacity Statement-R (3,000 Sheets)

12" x 18"/11" x 17"/Legal/Letter-R
(1,500 Sheets)

Lower Tray Letter/Executive/Statement/
Capacity Statement-R (250 Sheets)

12" x 18"/11" x 17"/Legal/Letter-R
(125 Sheets)

Paper Weight 14 lb. Bond to 140 lb. Index
(52 to 256 g/m²)

Lower Tray 14 lb. Bond to 110 lb. Cover
(52 to 300 g/m²)

Staple Position Corner, Double

Staple Capacity Corner Staple and Double Staple

Letter/
Executive 50 Sheets (24 lb. Bond (90 g/m²))

11" x 17/
Legal/
Letter-R 30 Sheets (24 lb. Bond (90 g/m²))

Staple-Free Staple
11" x 17/ 5 Sheets (14 to 17 lb. Bond (52 to 64 g/m²))

Letter 4 Sheets (17.3 to 21.7 lb. Bond (65 to 81.4 g/m²))

3 Sheets (21.7 to 28 lb. Bond (81.5 to 105 g/m²))

Staple On Demand 50 Sheets (24 lb. Bond (90 g/m²))

Booklet-Stitch Paper Size 12" x 18" (11" x 17" Legal, Letter-R,
Custom Size (7-3/4" x 10-5/8" to 12" x 8"
(195 mm x 270 mm to 304.8 mm x 457.2 mm))

Booklet-Stitch Staple Capacity 20 Sheets x 10 Sets (22 lb. Bond (81 g/m²))
(Including one cover sheet up to 140 lb.)
Index (256 g/m²)

Power Source From the Main Unit/85.6 W

Dimensions 25-1/8" x 24-1/2" x 45"

(W x D x H) (637 mm x 623 mm x 1142 mm)

Weight Approx. 25.7 lb. (11.7 kg)

INNER 2/3-HOLE PUNCHER-B1

(Requires the INNER FINISHER-H1)

Acceptable 14 lb. Bond to 110 lb. Cover

Punch Paper (52 to 300 g/m²)

Weight Acceptable Punch Paper Size

Two Holes 11" x 17", Legal, Letter, Letter-R, Executive

Three Holes 11" x 17", Letter, Executive

Power Source From the Main Unit

2/3-HOLE PUNCHER-A1

(Requires either the STAPLE FINISHER-Y1 or
BOOKLET FINISHER-Y1)

Acceptable 14 lb. Bond to 110 lb. Cover

Punch Paper (52 to 300 g/m²)

Weight Acceptable Punch Paper Size

Two Holes 11" x 17", Legal, Letter, Letter-R, Executive

Three Holes 11" x 17", Letter, Executive

Power Source From the Main Unit

Hardware Options

Card Readers

M-CARD PLUS PROXIMITY CARD READER
COPY CARD READER-F1
COPY CARD READER ATTACHMENT-B5

Others

CABINET TYPE-N
BUFFER PASS UNIT-L1
COPY TRAY-J2
UTILITY TRAY-B1
PLATEN COVER TYPE-W
PRINTER COVER-J1
TAB FEEDING ATTACHMENT-F1
USB KEYBOARD

Security Options

Document Security

DOCUMENT SCAN LOCK KIT-B1
SECURE WATERMARK-B
ENCRYPTED SECURE PRINT SOFTWARE-D1
IR-ADV SECURITY KIT-F1 (FOR IEEE 26031 COMMON CRITERIA CERTIFICATION)*

Data Security

HDD MIRRORING KIT-J1
1.5"/3.5" GB HDD-N1
1.5"/1 TB HDD-P1
REMOVABLE HDD KIT-AL1

System and Controller Options

Print Accessories

PCL INTERNATIONAL FONT SET-A1

Barcode Printing

BARCODE PRINTING KIT-D1

EFI-Fiery Based Controller

imagePASS-P1
ColorPASS-GX500 (IR-ADV C556D) (IR-ADV C555D) (only)
REMOVABLE HARD DISK DRIVE KIT-B1
FIERY IMPOSE
FIERY COMPOSE
FIERY IMPOSE AND COMPOSE

System Accessories

COPY CONTROL INTERFACE KIT-A
CONNECTION KIT-A1 (FOR BLUETOOTH LE
NFC KIT-D1
MEAP WEB CONNECTION KIT-G3

Fax Accessories

SUPER G3 FAX BOARD-A51
SUPER G3 2ND LINE FAX BOARD-A51
SUPER G3 3RD/4TH LINE FAX BOARD-A5
REMOTE FAX KIT-A1
IR FAX EXPANSION KIT-B1

Other Options

Accessibility Accessories

ADF ACCESS HANDLE-A1
VOICE GUIDANCE KIT-B1
VOICE OPERATION KIT-D1
BRAILLE LABEL KIT-F1

Staples

STAPLE-P1**
STAPLE CARTRIDGE-H1**

Footnotes

Some types of tracing paper cannot be used.
Time from device power-on to when ready to use is not programmed.
Includes main unit and either Cassette Feeding Unit (AM) High Capacity Cassette Feeding Unit (AS) or Tab Sheet Feeder. Includes main unit, consumables, and Cassette Feeding Unit (AM) PDF print from Web sites is supported.
FPIs can be printed covertly only from the Remote User Interface.
Requires the optional PCL International Font Set (A1).
Requires the optional Barcode Printing Kit (D1).
Other operating systems and environments, including iOS/iPadOS, macOS, and Linux, may be supported; some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your SAP account manager.
1.5 TB drive model not available with the mirrored drive option (H11114).
For details, see AT, at <http://www.epson.com/usa>.
Please visit www.epson.net.
GPR35: Toner also available for Color M1111. Yield is estimated at 3% coverage for 25,000 images. www.epson.com/usa.
Visit www.epson.com/usa for details on the 4,000 image per month page yield.
Visit www.epson.com/usa for details on the 4,000 image per month page yield.



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. AirPrint and the AirPrint logo are trademarks of Apple Inc., "Adobe" and PostScript® 3™ are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Microsoft® and PowerPoint® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. PCL® is a registered trademark of Hewlett-Packard Company. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2017 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.



0817R2-PA55xx555-PDF-IH