

## Feature comparison

Throughput Speeds at 200 dpi/300 dpi † (landscape, A4 size, black and white/ grayscale/color)	<b>i3200</b> ADF: Up to 50 ppm <b>i3250</b> ADF: Up to 50 ppm	<b>i3300</b> ADF: Up to 70 ppm	<b>i3400</b> ADF: Up to 90 ppm <b>i3450</b> ADF: Up to 90 ppm	<b>i3500</b> ADF: Up to 110 ppm
---	--	--------------------------------	--	---------------------------------

Recommended Daily Volume	<b>i3200/i3250</b> ADF: Up to 15,000 pages per day <b>i3250</b> integrated A4 size flatbed: 100 pages per day	<b>i3300</b> ADF: Up to 17,500 pages per day	<b>i3400/i3450</b> ADF: Up to 20,000 pages per day <b>i3450</b> integrated A4 size flatbed: 100 pages per day	<b>i3500</b> ADF: Up to 25,000 pages per day
--------------------------	--	---	--	---

## Shared features

Scanning Technology	Dual CCD; Grayscale output bit depth is 256 levels (8-bit); color capture bit depth is 48 bits (16 x 3); color output bit depth is 24 bits (8 x 3)
Optical Resolution	1200 dpi
Output Resolution	100 / 150 / 200 / 240 / 250 / 300 / 400 / 500 / 600 dpi
Illumination	Dual LED
Operator Control Panel	Graphical LCD display with four operator control buttons
Maximum/Minimum Document Width	Auto-feed: 305 mm (12 in.) / 63.5 mm (2.5 in.) Hand-feed: 305 mm (12 in.) / 50 mm (2 in.)
Maximum/Minimum Document Length	Auto-feed: 863.6 mm (34 in.) / 63.5 mm (2.5 in.) Hand-feed: 863.6 mm (34 in.) / 50 mm (2 in.) (rear exit only) Long document mode: 4.1 meters (160 in.) maximum length (The scanners support continuous scanning mode)
Paper Thickness and Weight	34-413 g/m <sup>2</sup> paper
Feeder/Elevator	<b>i3200/i3250/i3300/i3400/i3450</b> : Up to 250 sheets of 80 g/m <sup>2</sup> paper; <b>i3500</b> : up to 300 sheets of 80 g/m <sup>2</sup> paper
Paper Path Options	Documents can exit into the front output tray, or at the rear of the scanner if the straight-through paper path option is manually selected
Multi-feed Detection	Ultrasonic multi-feed detection; Intelligent Document Protection
Connectivity	USB 2.0; USB 3.0 compatible
Software Support	Fully supported by <b>Kodak Capture Pro Software</b> and <b>Kodak Asset Management Software</b> Windows bundled software: <b>TWAIN</b> , <b>ISIS</b> , and <b>WIA</b> drivers; <b>Kodak Capture Pro Software Limited Edition</b> ; Smart Touch ( <b>Linux SANE</b> and <b>TWAIN</b> drivers available from <a href="http://www.kodakalaris.com/go/scanonlinux">www.kodakalaris.com/go/scanonlinux</a> ); <b>Kofax</b> certified <b>Mac</b> bundled software**: <b>NewSoft Presto! PageManager</b> ; <b>TWAIN</b> driver* (available via web download only)
Barcode Reading	One per page: Interleaved 2 of 5, Code 3 of 9, Code 128, Codabar, UPC-A, UPC-E, EAN-13, EAN-8, PDF417
Features in the Scanner	Barcode reading; Perfect Page scanning; iThresholding; adaptive threshold processing; deskew; autotrim; relative cropping; aggressive cropping; electronic color dropout; dual stream scanning; interactive color, brightness and contrast adjustment; automatic orientation; automatic color detection; intelligent background color smoothing; intelligent image edge fill; image merge; content-based blank page detection; streak filtering; image hole fill; sharpness filter; auto brightness, special document mode; continuous scanning mode; toggle patch; auto photo cropping; segmented bitonal images
File Format Outputs	Single and multi-page TIFF, JPEG, RTF, BMP, PDF, searchable PDF
Warranty	Check with your local sales representative
Electrical Requirements	100-240 V (International); 50-60 Hz
Power Consumption	Off mode: <0.5 watts; Running: <49 watts; Sleep mode: <2.8 watts
Environmental Factors	<b>Energy Star</b> qualified scanners Operating temperature: 15-35°C (59-95°F); Operating humidity: 15% to 80% RH
Acoustical Noise (operator position sound pressure level)	Off or Ready mode: <30 dB(A) Operating mode: <60 dB(A); <66dB(A) i3500 only
Recommended PC Configuration	<b>Intel Core</b> i7, 3.4 GHz processor or higher, 4 GB RAM or higher, USB 2.0 ( <b>Windows</b> and <b>Linux</b> ) <b>Intel Core</b> i7 processor, 2.0 GHz quad-core, 4 GB of RAM, USB 2.0 ( <b>Mac</b> )
Supported Operating Systems	<b>Windows 10</b> (32-bit and 64-bit), <b>Windows 8.1</b> (32-bit and 64-bit), <b>Windows 8</b> (32-bit and 64-bit), <b>Windows 7</b> SP1 (32-bit and 64-bit), <b>Windows Vista</b> SP2 (32-bit and 64-bit), <b>Windows XP</b> (customer validated - not supported by Kodak Alaris because <b>Microsoft</b> discontinued support in 2014), <b>Ubuntu</b> 14.04 (LTS)*, <b>Mac OS</b> v10.8, 10.9, 10.10*
Consumables Available	Roller cleaning pads, <b>Staticide</b> Wipes, consumables kit (includes feed module, separation module, separation pad)
Accessories/Options	<b>Kodak Legal Size Flatbed Accessory</b> ; <b>Kodak A3 Size Flatbed Accessory</b> ; document imprinting accessory (rear-side, post-scan imprinting of up to 40 alphanumeric characters, with 11 imprinting positions)
Dimensions	<b>i3200/i3300/i3400/i3500</b> : Height: 9.4 in. / 23.8 cm; Width: 17 in. / 43.18 cm; Depth (with input tray closed): 14.6 in. / 37.1 cm <b>i3250/i3450</b> : Height: 10.2 in. / 25.7 cm; Width: 17 in. / 43.18 cm; Depth (with input tray closed): 14.6 in. / 37.1 cm
Weight	<b>i3200/i3300/i3400/i3500</b> : Weight: 35 lbs / 15.8 kg <b>i3250/i3450</b> : Weight: 39 lbs / 17.7 kg

† Throughput speeds may vary depending on your choice of driver, application software, operating system and PC

\* Smart Touch functionality is not supported on these Operating Systems

\*\* Available for the i3200/i3250, i3300, i3400/i3450

## Want to learn more?

[www.kodakalaris.com/go/i3000Series](http://www.kodakalaris.com/go/i3000Series)

## Kodak Alaris Inc.

2400 Mt. Read Blvd., Rochester, NY 14615, USA

1-800-944-6171

## Kodak Alaris Operations Canada Inc.

Mississauga, Ontario, Canada L5W 0A5

1-800-944-6171



See Awards Brochure →

**Kodak**Service & Support  
for Document Imaging Solutions**Kodak alaris**© 2016 Kodak Alaris Inc.  
The Kodak trademark and trade dress are used  
under license from Eastman Kodak Company.  
6/16